

Standard Hoses

Air Hoses

Hunting supplies the standard air hoses detailed in the table below.

All hoses are pressure tested, tagged with the year of manufacture, working/test/ burst pressures and HESWI part number. Additionally, hoses to be used with ATEX certified equipment are of the anti-static type.

The hoses can be supplied with compatible quick connections detailed in the quick connections table below. Non-standard hoses can also be supplied on request.

AIR HOSES				
Description	N.B. (in)	MWP (psi)	Length (ft)	Part No.
3/4" N.B. AIR HOSE, 250 psi M.W.P., 25 feet LG., 0.75" NPT MALE x MALE ENDS, SINGLE LINE	0.75	250	25	371-0750-025
3/4" N.B. AIR HOSE, 250 psi M.W.P., 50 feet LG., 0.75" NPT MALE x MALE ENDS, SINGLE LINE	0.75	250	50	371-0750-050
3/4" N.B. AIR HOSE, 250 psi M.W.P., 75 feet LG., 0.75" NPT MALE x MALE ENDS, SINGLE LINE	0.75	250	75	371-0750-075

Hydraulic Hoses

Hunting supplies the standard hydraulic hoses detailed in the table below. All hoses have a minimum burst pressure 4x greater than the working pressure of the hose.

All hoses are pressure tested, tagged with the year of manufacture, working/test/ burst pressures and HESWI part number. Additionally, hoses to be used with ATEX certified equipment are tested for electrical conductivity.

The hoses can be supplied with compatible quick connections detailed in the quick connections table below. Non-standard hoses can also be supplied on request.

(See chart overleaf)



Standard Hoses

Wireline Operations - Mechanical Plant Accessories

HYDRAULIC HOSES				
Description	N.B. (in)	MWP (psi)	Length (ft)	Part No.
0.25" N.B. HOSE, 4K psi M.W.P., 4 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE (BOP BRIDLE)	0.25	4	4	371-1250-004
0.25" N.B. HOSE, 4K psi M.W.P., 8 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE (BOP BRIDLE)	0.25	4	8	371-1250-008
0.25" N.B. HOSE, 4K psi M.W.P., 25 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE	0.25	4	25	371-1250-025
0.25" N.B. HOSE, 4K psi M.W.P., 50 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE	0.25	4	50	371-1250-050
0.25" N.B. HOSE, 4K psi M.W.P., 50 feet LG., #4 JIC FEMALE x FEMALE ENDS, TWIN LINE	0.25	4	50	371-1250-050-TWIN
0.25" N.B. HOSE, 4K psi M.W.P., 75 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE	0.25	4	75	371-1250-075
0.25" N.B. HOSE, 4K psi M.W.P., 75 feet LG., #4 JIC FEMALE x FEMALE ENDS, TWIN LINE	0.25	4	75	371-1250-075-TWIN
0.25" N.B. HOSE, 4K psi M.W.P., 100 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE	0.25	4	100	371-1250-100
0.25" N.B. HOSE, 4K psi M.W.P., 100 feet LG., #4 JIC FEMALE x FEMALE ENDS, TWIN LINE	0.25	4	100	371-1250-100-TWIN
0.25" N.B. HOSE, 4K psi M.W.P., 125 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE	0.25	4	125	371-1250-125
0.25" N.B. HOSE, 4K psi M.W.P., 125 feet LG., #4 JIC FEMALE x FEMALE ENDS, TWIN LINE	0.25	4	125	371-1250-125-TWIN
0.25" N.B. HOSE, 5K psi M.W.P., 25 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE*	0.25	5	25	371-2250-025
0.25" N.B. HOSE, 5K psi M.W.P., 50 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE*	0.25	5	50	371-2250-050
0.25" N.B. HOSE, 5K psi M.W.P., 75 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE*	0.25	5	75	371-2250-075
0.25" N.B. HOSE, 5K psi M.W.P., 100 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE*	0.25	5	100	371-2250-100
0.25" N.B. HOSE, 5K psi M.W.P., 125 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE*	0.25	5	125	371-2250-125
0.25" N.B. HOSE, 10K psi M.W.P., 25 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE	0.25	10	25	371-3250-025
0.25" N.B. HOSE, 10K psi M.W.P., 50 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE	0.25	10	50	371-3250-050
0.25" N.B. HOSE, 10K psi M.W.P., 75 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE	0.25	10	75	371-3250-075
0.25" N.B. HOSE, 10K psi M.W.P., 100 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE	0.25	10	100	371-3250-100
0.25" N.B. HOSE, 10K psi M.W.P., 125 feet LG., 0.25" NPT MALE x #4 JIC FEMALE ENDS, SINGLE LINE	0.25	10	125	371-3250-125
0.188" N.B. HOSE, 25K psi M.W.P., 25 feet LG., 0.375" MEDIUM PRESSURE MALE x MALE ENDS, SINGLE LINE	0.188	25	25	371-6188-025
0.188" N.B. HOSE, 25K psi M.W.P., 50 feet LG., 0.375" MEDIUM PRESSURE MALE x MALE ENDS, SINGLE LINE	0.188	25	50	371-6188-050
0.188" N.B. HOSE, 25K psi M.W.P., 75 feet LG., 0.375" MEDIUM PRESSURE MALE x MALE ENDS, SINGLE LINE	0.188	25	75	371-6188-075
0.188" N.B. HOSE, 25K psi M.W.P., 100 feet LG., 0.375" MEDIUM PRESSURE MALE x MALE ENDS, SINGLE LINE	0.188	25	100	371-6188-100
0.188" N.B. HOSE, 25K psi M.W.P., 125 feet LG., 0.375" MEDIUM PRESSURE MALE x MALE ENDS, SINGLE LINE	0.188	25	125	371-6188-125
0.375" N.B. HOSE, 5K psi M.W.P., 25 feet LG., #8JIC FEMALE x FEMALE ENDS, SINGLE LINE	0.375	5	25	371-2375-025
0.375" N.B. HOSE, 5K psi M.W.P., 50 feet LG., #8JIC FEMALE x FEMALE ENDS, SINGLE LINE	0.375	5	50	371-2375-050
0.375" N.B. HOSE, 5K psi M.W.P., 75 feet LG., #8JIC FEMALE x FEMALE ENDS, SINGLE LINE	0.375	5	75	371-2375-075
0.375" N.B. HOSE, 5K psi M.W.P., 100 feet LG., #8JIC FEMALE x FEMALE ENDS, SINGLE LINE	0.375	5	100	371-2375-100
0.375" N.B. HOSE, 5K psi M.W.P., 125 feet LG., #8JIC FEMALE x FEMALE ENDS, SINGLE LINE	0.375	5	125	371-2375-125
0.375" N.B. HOSE, 10K psi M.W.P., 25 feet LG., #8JIC FEMALE x FEMALE ENDS, SINGLE LINE	0.375	10	25	371-3375-025
0.375" N.B. HOSE, 10K psi M.W.P., 50 feet LG., #8JIC FEMALE x FEMALE ENDS, SINGLE LINE	0.375	10	50	371-3375-050
0.375" N.B. HOSE, 10K psi M.W.P., 75 feet LG., #8JIC FEMALE x FEMALE ENDS, SINGLE LINE	0.375	10	75	371-3375-075
0.375" N.B. HOSE, 10K psi M.W.P., 100 feet LG., #8JIC FEMALE x FEMALE ENDS, SINGLE LINE	0.375	10	100	371-3375-100
0.375" N.B. HOSE, 10K psi M.W.P., 125 feet LG., #8JIC FEMALE x FEMALE ENDS, SINGLE LINE	0.375	10	125	371-3375-125
0.313" N.B. HOSE, 15K psi M.W.P., 25 feet LG., 0.563" MEDIUM PRESSURE MALE x MALE ENDS, SINGLE LINE	0.313	15	25	371-4313-025
0.313" N.B. HOSE, 15K psi M.W.P., 50 feet LG., 0.563" MEDIUM PRESSURE MALE x MALE ENDS, SINGLE LINE	0.313	15	50	371-4313-050
0.313" N.B. HOSE, 15K psi M.W.P., 75 feet LG., 0.563" MEDIUM PRESSURE MALE x MALE ENDS, SINGLE LINE	0.313	15	75	371-4313-075
0.313" N.B. HOSE, 15K psi M.W.P., 100 feet LG., 0.563" MEDIUM PRESSURE MALE x MALE ENDS, SINGLE LINE	0.313	15	100	371-4313-100
0.313" N.B. HOSE, 15K psi M.W.P., 125 feet LG., 0.563" MEDIUM PRESSURE MALE x MALE ENDS, SINGLE LINE	0.313	15	125	371-4313-125
0.50" N.B. HOSE, 5K psi M.W.P., 25 feet LG., 0.5" NPT MALE x MALE ENDS, SINGLE LINE	0.50	5	25	371-2500-025
0.50" N.B. HOSE, 5K psi M.W.P., 50 feet LG., 0.5" NPT MALE x MALE ENDS, SINGLE LINE	0.50	5	50	371-2500-050
0.50" N.B. HOSE, 5K psi M.W.P., 75 feet LG., 0.5" NPT MALE x MALE ENDS, SINGLE LINE	0.50	5	75	371-2500-075
0.50" N.B. HOSE, 5K psi M.W.P., 100 feet LG., 0.5" NPT MALE x MALE ENDS, SINGLE LINE	0.50	5	100	371-2500-100
0.50" N.B. HOSE, 5K psi M.W.P., 125 feet LG., 0.5" NPT MALE x MALE ENDS, SINGLE LINE	0.50	5	125	371-2500-125
0.50" N.B. HOSE, 10K psi M.W.P., 25 feet LG., 0.5" BSPP FEMALE x FEMALE ENDS, SINGLE LINE	0.50	10	25	371-3500-025
0.50" N.B. HOSE, 10K psi M.W.P., 50 feet LG., 0.5" BSPP FEMALE x FEMALE ENDS, SINGLE LINE	0.50	10	50	371-3500-050
0.50" N.B. HOSE, 10K psi M.W.P., 75 feet LG., 0.5" BSPP FEMALE x FEMALE ENDS, SINGLE LINE	0.50	10	75	371-3500-075
0.50" N.B. HOSE, 10K psi M.W.P., 100 feet LG., 0.5" BSPP FEMALE x FEMALE ENDS, SINGLE LINE	0.50	10	100	371-3500-100
0.50" N.B. HOSE, 10K psi M.W.P., 125 feet LG., 0.5" BSPP FEMALE x FEMALE ENDS, SINGLE LINE	0.50	10	125	371-3500-125

* Not suitable for ATEX certified equipment

