

Spoolable Connector

Thru-Tubing Technology | Coiled Tubing Connectors

Features

- Robust, cost effective joining of two sections of coil
- Available in coil sizes from 1-1/4 inches to 2-7/8 inches
- One-piece design

Benefits

- Available in both dimple-on and roll-on
- Available for all coil sizes

The Spoolable Connector with one-piece design provides a robust, cost effective means of joining two sections of coil for the purposes of retrieving coil and spooling back onto the reel. They are available in both dimple-on and roll-on styles.

The roll-on design incorporates three O-ring grooves providing added security in high-pressure applications. There are also three crimping grooves to give improved tensile strength.

The Spoolable Connector is available for any combination of coil tubing.

The Spoolable Connector is not qualified for and should not be used in downhole operational applications.



Spoolable Connector / Product Code WT-1301 & 1304

Coil Tubing OD in inches	1-1/2"	1-3/4"	2"	2-3/8"	2-7/8"
Wall Thickness	TBA	TBA	TBA	TBA	TBA
ID in inches	0.563	0.750	1.060	1.313	1.813
Tensile Strength (Lbs)	38,390	69,080	77,440	144,800	165,110
Length in feet	1.54	1.46	1.54	1.54	1.54
Working Pressure in Psi	5K	5K	5K	5K	5K

Properties quoted for standard service materials.